

Fast-Covering Paper

Pure cellulose paper roll + adhesive tape.



ADVANTAGES AND PERFORMANCES

- Professional masking of floors and all kinds of surfaces while painting
- Adhesion with light pressure

TECHNICAL PROPERTIES

test method

Weight:	35 g/m ²	ISO - 536
Weight tolerance:	± 1,5 g/m ²	ISO - 536
Tensile strength:	MD 3,78 kN/m - CD 1,54 kN/m	EN - ISO - 1924 - 2
Tear resistance:	MD 210 mN - CD 280 mN	EN - 21974
Water absorbency (Cobb60):	up to 30 g/m ²	ISO - 535
Moisture:	5 - 9 %	ISO - 287

The above values are the result of arithmetic averages from tests on sample productions and are not legally binding.

ADHESIVE TAPE

Paper adhesive tape for professional masking; suitable for applications at medium temperatures in the car body repair, building and construction industries.

Backing:	71 g/m ² impregnated white paper	Adhesive:	natural dry rubber and solvent resins
-----------------	---	------------------	---------------------------------------

TECHNICAL PROPERTIES

Total thickness:	150 µm
Elongation at break:	8 %
Tensile strength:	95 N/25 mm
Adhesion to steel:	3,5 N/25 mm
Temperature resistance:	up to 80 °C for 30 minutes

The above values are the result of arithmetic averages from tests on sample productions and are not legally binding.

ARTICLES, DIMENSIONS AND BARCODES

dimensions

pieces per box

barcode

cod. 1700:	10 cm x 20 m	75	8051499033163
cod. 1702:	18 cm x 20 m	50	8051499033170
cod. 1703:	30 cm x 20 m	25	8051499033187

The a.m. values may be changed at any moment for production needs or technical updates.

rev. 01_May 2019