

## Mask E HM

Masking tape compatible with the most common water- and solvent-based paints. It is suitable for applications at room temperature in the building and indoor painting industries, as well as for general purpose and do-it-yourself works.



### ADVANTAGES AND PERFORMANCES

- High tack adhesive
- Hand tearable
- Easy to unwind

### TECHNICAL PROPERTIES

		tolerance	test method
Adhesive:	Hot Melt		
Total thickness:	95 µm	± 10 %	AFERA 5006
Adhesion to steel:	min. 2 N/cm		AFERA 5001
Tensile strength:	min. 28 N/cm		AFERA 5004
Elongation at break:	min. 7 %		AFERA 5004
Temperature resistance:	room temperature		
Colour:	white and yellow		

The above values are the result of arithmetic averages from tests on sample productions and are not legally binding.

### ARTICLES, DIMENSIONS AND BARCODES

	dimensions	pieces per box	barcode
Mask E HM white:	19 mm x 50 m	96 rolls	8051499030162
Mask E HM white:	25 mm x 50 m	72 rolls	8051499030179
Mask E HM white:	30 mm x 50 m	60 rolls	8051499030186
Mask E HM white:	38 mm x 50 m	48 rolls	8051499030193
Mask E HM white:	50 mm x 50 m	36 rolls	8051499030209
Mask E HM yellow:	19 mm x 50 m	96 rolls	8051499030384
Mask E HM yellow:	25 mm x 50 m	72 rolls	8051499030391
Mask E HM yellow:	30 mm x 50 m	60 rolls	8051499030407
Mask E HM yellow:	38 mm x 50 m	48 rolls	8051499030414
Mask E HM yellow:	50 mm x 50 m	36 rolls	8051499030421

### OUR PROPOSAL OF PACKAGING

- Sleeve with B/W or coloured (up to 5 colours) barcode label
- Harmonica
- Tower

### RECOMMENDATIONS

It's a good rule to use the product within 6 months from purchase, because the unwinding force of the tape increases with time. The product must be stored in its box in a dry location protected from sunlight, at about 15 °C - 25 °C and 50% relative humidity. If stored in different conditions, the product must be reconditioned. After application, the removal of the tape must be done slowly without tears. Before applying the tape, always check if the surface is clean. Euromask disclaims any liability for any direct or indirect damage coming from the misuse of the product. Under normal conditions, the tape is not toxic and is not approved for medical use.

The a.m. values may be changed at any moment for production needs or technical updates.

rev. 01\_May 2019