



PVC 32 printed

PVC packaging tape with natural rubber adhesive; we can customize it with your company logo, a message or a slogan, according to your needs.

ADVANTAGES AND PERFORMANCES

- Suitable for long-term storage of heavy weights
- Good adhesiveness on irregular surfaces
- For manual and automatic use

TECHNICAL PROPERTIES

		tolerance	test method
Backing:	PVC		
Adhesive:	solvent-based natural rubber		
Total thickness:	53 µm	± 10 %	
Film thickness:	32 µm	± 10 %	
Tensile strength:	min. 45 N/cm		AFERA 5004
Elongation at break:	min. 70 %		AFERA 5004
Adhesion to steel:	min. 1,7 N/cm		AFERA 5001
Temperature resistance:	room temperature		
Colour:	brown, white and transparent		

The above values are the result of arithmetic averages from tests on sample productions and are not legally binding.

OUR PROPOSAL OF PACKAGING

- Loose roll

RECOMMENDATIONS

It's a good rule to use the product within 6 months from purchase, because the unwinding force of the tape increases with time. The product must be stored in its box in a dry location protected from sunlight, at about 15 °C - 25 °C and 50% relative humidity. If stored in different conditions, the product must be reconditioned. After application, the removal of the tape must be done slowly without tears. Before applying the tape, always check if the surface is clean. Euromask disclaims any liability for any direct or indirect damage coming from the misuse of the product. Under normal conditions, the tape is not toxic and is not approved for medical use.

The a.m. values may be changed at any moment for production needs or technical updates.