

## Mask WR

Professional waterproof masking tape, resistant to high temperatures (up to 90 °C for 1 hour / up to 110 °C for 30 minutes). Thanks to these features, this product is suitable for applications in the building, car body repair and industrial painting sectors.

It has a crêpe paper backing and solvent-based adhesive.



### ADVANTAGES AND PERFORMANCES

- High resistance to water and moisture
- Good adhesiveness on irregular surfaces
- Residue-free removal
- Compatible with the most common paints
- Removable without tearing

### TECHNICAL PROPERTIES

		tolleranza	metodo di prova
Backing:	crêpe paper		
Adhesive:	natural rubber and solvent resins		
Total weight:	103 g/m <sup>2</sup>	± 10 %	ISO 536
Total thickness:	135 µm	± 10 %	AFERA 5006
Tensile strength:	min. 38 N/cm		AFERA 5004
Elongation at break:	min. 8 %		AFERA 5004
Adhesion to steel:	min. 2,3 N/cm		AFERA 5001
Temperature resistance:	up to 90 °C for 1 h / up to 110 °C for 30 min		
Colour:	lime, green and red		

The above values are the result of arithmetic averages from tests on sample productions and are not legally binding.

### ARTICLES AND DIMENSIONS

	dimensions	pieces per box
Mask WR lime/green/red:	19 mm x 50 m	96 rolls
Mask WR lime/green/red:	25 mm x 50 m	72 rolls
Mask WR lime/green/red:	30 mm x 50 m	60 rolls
Mask WR lime/green/red:	38 mm x 50 m	48 rolls
Mask WR lime/green/red:	50 mm x 50 m	36 rolls

### OUR PROPOSAL OF PACKAGING

- Sleeve
- Harmonica

### RECOMMENDATIONS

It's a good rule to use the product within 6 months from purchase, because the unwinding force of the tape increases with time. The product must be stored in its box in a dry location protected from sunlight, at about 15 °C - 25 °C and 50% relative humidity. If stored in different conditions, the product must be reconditioned. After application, the removal of the tape must be done slowly without tears. Before applying the tape, always check if the surface is clean. Euromask disclaims any liability for any direct or indirect damage coming from the misuse of the product. Under normal conditions, the tape is not toxic and is not approved for medical use.

The a.m. values may be changed at any moment for production needs or technical updates.

rev. 31\_July 2019