



Washi Tape HP

Masking tape made of pure Japanese paper; specially designed for outdoor applications, to obtain extremely accurate paint edges. Thanks to its special adhesive formula, it guarantees weather, extreme temperatures and UV (up to 12 weeks) resistance.

ADVANTAGES AND PERFORMANCES

- Specially designed for outdoor use
- Accurate paint edges
- Removable without tearing
- UV resistance up to 12 weeks

TECHNICAL PROPERTIES

		tolerance	test method
Backing:	Japanese paper		
Adhesive:	clear acrylic adhesive		
Total weight:	83 g/m ²	± 10 %	ISO 536
Total thickness:	85 µm	± 10 %	AFERA 5006
Tensile strength:	min. 24 N/cm		AFERA 5004
Elongation at break:	min. 3 %		AFERA 5004
Adhesion to steel:	min. 1,2 N/cm		AFERA 5001
Temperature resistance:	extreme weather conditions		
Colour:	blue		

The above values are the result of arithmetic averages from tests on sample productions and are not legally binding.

ARTICLES, DIMENSIONS AND BARCODES

	dimensions	pieces per box	barcode
Washi Tape HP:	19 mm x 50 m	48 rolls	8051499033675
Washi Tape HP:	25 mm x 50 m	36 rolls	8051499033637
Washi Tape HP:	30 mm x 50 m	32 rolls	8051499033644
Washi Tape HP:	38 mm x 50 m	24 rolls	8051499033804
Washi Tape HP:	50 mm x 50 m	24 rolls	8051499033835

OUR PROPOSAL OF PACKAGING

- Sleeve with B/W or coloured (up to 5 colours) barcode label
- Harmonica

RECOMMENDATIONS

It's a good rule to use the product within 6 months from purchase, because the unwinding force of the tape increases with time. The product must be stored in its box in a dry location protected from sunlight, at about 15 °C - 25 °C and 50% relative humidity. If stored in different conditions, the product must be reconditioned. After application, the removal of the tape must be done slowly without tears. Before applying the tape, always check if the surface is clean. Euromask disclaims any liability for any direct or indirect damage coming from the misuse of the product. Under normal conditions, the tape is not toxic and is not approved for medical use.

The a.m. values may be changed at any moment for production needs or technical updates.

rev. 01_May 2019