

Washi Tape

Masking tape made of pure Japanese paper; suitable for professional applications in the building sector and for indoor complex and precision works, that require extremely accurate paint edges. Thanks to the properties of the paper and the acrylic adhesive, it guarantees high performances up to 120 °C and UV resistance (up to 3 months).



ADVANTAGES AND PERFORMANCES

- Accurate paint edges
- Compatible with the most common paints
- Removable without tearing
- UV resistance up to 3 months

TECHNICAL PROPERTIES

		tolerance	test method
Backing:	Japanese paper		
Adhesive:	clear acrylic adhesive		
Total weight:	83 g/m ²	± 10 %	ISO 536
Total thickness:	85 µm	± 10 %	AFERA 5006
Tensile strength:	min. 24 N/cm		AFERA 5004
Elongation at break:	min. 3 %		AFERA 5004
Adhesion to steel:	min. 1,1 N/cm		AFERA 5001
Temperature resistance:	up to 120 °C		
Colour:	yellow		

The above values are the result of arithmetic averages from tests on sample productions and are not legally binding.

ARTICLES, DIMENSIONS AND BARCODES

	dimensions	pieces per box	barcode
Washi Tape:	19 mm x 50 m	48 rolls	8051499033651
Washi Tape:	25 mm x 50 m	36 rolls	8051499033590
Washi Tape:	30 mm x 50 m	32 rolls	8051499033606
Washi Tape:	38 mm x 50 m	24 rolls	8051499033781
Washi Tape:	50 mm x 50 m	24 rolls	8051499033811

OUR PROPOSAL OF PACKAGING

- Sleeve with B/W or coloured (up to 5 colours) barcode label
- Harmonica

RECOMMENDATIONS

It's a good rule to use the product within 6 months from purchase, because the unwinding force of the tape increases with time. The product must be stored in its box in a dry location protected from sunlight, at about 15 °C - 25 °C and 50% relative humidity. If stored in different conditions, the product must be reconditioned. After application, the removal of the tape must be done slowly without tears. Before applying the tape, always check if the surface is clean. Euromask disclaims any liability for any direct or indirect damage coming from the misuse of the product. Under normal conditions, the tape is not toxic and is not approved for medical use.

The a.m. values may be changed at any moment for production needs or technical updates.

rev.01_April 2020