



## Duct 220-S

Natural Rubber Adhesive Tape.  
 Polyester (PET) polyethylene (PE) film.  
 High performance on irregular surfaces.

### ADVANTAGES AND PERFORMANCES

- General maintenance.
- Construction sector: excellent for sandblasting.
- Excellent grip on porous and irregular surfaces.

### TECHNICAL PROPERTIES

		tolerance	test method
Backing/Adhesive:	PE film/natural rubber		
Total thickness:	220 µm	± 10 %	AFERA 5006
Tensile strength:	min. 77 N/cm		AFERA 5004
Elongation at break:	15 %		AFERA 5004
Adhesion to steel:	11,5N/cm		AFERA 5001
Colour:	yellow		

The above values are the result of arithmetic averages from tests on sample productions and are not legally binding.

### ARTICLES, DIMENSIONS AND BARCODES

	dimensions	pieces per box	barcode
Duct 220-S yellow:	50 mm x 50 m	24 rolls	8051499033903

### OUR PROPOSAL OF PACKAGING

- Single sleeve.

### RECOMMENDATIONS

It's a good rule to use the product within 6 months from purchase, because the unwinding force of the tape increases with time. The product must be stored in its box in a dry location protected from sunlight, at about 15 °C - 25 °C and 50% relative humidity. If stored in different conditions, the product must be reconditioned. After application, the removal of the tape must be done slowly without tears. Before applying the tape, always check if the surface is clean. Euromask disclaims any liability for any direct or indirect damage coming from the misuse of the product. Under normal conditions, the tape is not toxic and is not approved for medical use.

The a.m. values may be changed at any moment for production needs or technical updates.



rev. 01\_Jan 2024