



Ecomask E 60 Brown

Masking Tape.
 Brown paper.
 Natural rubber.

BENEFITS AND PERFORMANCE

- Good Adhesive.
- Removable without breaking, created for closing boxes.
- Impregnated paper for maximum conformity.

TECHNICAL SPECIFICATIONS

		tolerance	test methods
Adhesive:	natural rubber		
Total thickness:	108 µm	± 10 %	AFERA 5006
Breaking load:	min 25 N/cm		AFERA 5004
Elongation:	min 7 %		AFERA 5004
Adhesion to steel:	min 2,0 N/cm		AFERA 5001
Resistenza alla temperatura:	60°C		
Color:	brown		
Available size:	standard		

The values obtained are the result of mathematical averages relating to the analyzes carried out on the productions and are not legally binding..

ARTICLES, DIMENSIONS AND BARCODES

	dimensions	pieces per box	barcodes
Ecomask E 60 Brown:	50 mm x 50 m	36 rolls	8051499033460

PACKAGING PROPOSAL

- Harmonica

RACCOMANDAZIONI

It's a good rule to use the product within 6 months from purchase, because the unwinding force of the tape increases with time. The product must be stored in its box in a dry location protected from sunlight, at about 15 °C - 25 °C and 50% relative humidity. If stored in different conditions, the product must be reconditioned. After application, the removal of the tape must be done slowly without tears. Before applying the tape, always check if the surface is clean. Euromask disclaims any liability for any direct or indirect damage coming from the misuse of the product. Under normal conditions, the tape is not toxic and is not approved for medical use.

The a.m. values may be changed at any moment for production needs or technical updates.



rev.01_Jan 2024