

Mask E 6020

Masking tape suitable for applications in the indoor painting, building and construction industries, as well as for general purpose works, that don't require resistance to high temperatures (up to 60 °C).



ADVANTAGES AND PERFORMANCES

- Good adhesiveness on irregular surfaces.
- Residue-free removal.
- Saturated paper for maximum conformability.
- Compatible with the most common paints.
- Hand tearable.
- Removable without tearing.

TECHNICAL PROPERTIES

		tolerance	test method
Adhesive:	natural rubber and solvent resins		
Total weight:	80 g/m ²	± 10 %	ISO 536
Total thickness:	118 µm	± 10 %	AFERA 5006
Tensile strength:	min. 32 N/cm		AFERA 5004
Elongation at break:	min. 7 %		AFERA 5004
Adhesion to steel:	min. 2,1 N/cm		AFERA 5001
Temperature resistance:	up to 60 °C		
Colour:	white and yellow		

The above values are the result of arithmetic averages from tests on sample productions and are not legally binding.

ARTICLES, DIMENSIONS AND BARCODES

	dimensions	pieces per box	barcode
Mask E 6020 white:	19 mm x 50 m	96 rolls	8051499034214
Mask E 6020 white:	25 mm x 50 m	72 rolls	8051499034221
Mask E 6020 white:	30 mm x 50 m	60 rolls	8051499034238
Mask E 6020 white:	38 mm x 50 m	48 rolls	8051499034245
Mask E 6020 white:	50 mm x 50 m	36 rolls	8051499034252
Mask E 6020 yellow:	19 mm x 50 m	96 rolls	8051499034269
Mask E 6020 yellow:	25 mm x 50 m	72 rolls	8051499034276
Mask E 6020 yellow:	30 mm x 50 m	60 rolls	8051499034283
Mask E 6020 yellow:	38 mm x 50 m	48 rolls	8051499034290
Mask E 6020 yellow:	50 mm x 50 m	36 rolls	8051499034306

OUR PROPOSAL OF PACKAGING

- Sleeve with B/W or coloured (up to 5 colours) barcode label.
- Harmonica.
- Tower.

RECOMMENDATIONS

It's a good rule to use the product within 6 months from purchase, because the unwinding force of the tape increases with time. The product must be stored in its box in a dry location protected from sunlight, at about 15 °C - 25 °C and 50% relative humidity. If stored in different conditions, the product must be reconditioned. After application, the removal of the tape must be done slowly without tears. Before applying the tape, always check if the surface is clean. Euromask disclaims any liability for any direct or indirect damage coming from the misuse of the product. Under normal conditions, the tape is not toxic and is not approved for medical use.

The a.m. values may be changed at any moment for production needs or technical updates.



rev.01_Jan 2024