



## Washi Tape LT

Masking tape made of pure Japanese paper; it guarantees high performances on freshly painted surfaces, when high paint precision is needed to obtain extremely accurate edges, without waiting for the standard drying time. Suitable for applications that require 'low tack' properties, such as renovations, touch-ups and final touches on wallpaper and delicate and wet surfaces.

### ADVANTAGES AND PERFORMANCES

- Excellent for accurate decoration.
- Removable without tearing.
- UV resistance up to 7 days.

### TECHNICAL PROPERTIES

		tolerance	test method
Backing:	japanese paper		
Adhesive:	clear acrylic adhesive		
Total weight:	70 g/m <sup>2</sup>	± 10 %	ISO 536
Total thickness:	75 µm	± 10 %	AFERA 5006
Tensile strength:	min. 25 N/cm		AFERA 5004
Elongation at break:	min. 3 %		AFERA 5004
Adhesion to steel:	min. 0,9 N/cm		AFERA 5001
Temperature resistance:	room temperature		
Colour:	violet		

The above values are the result of arithmetic averages from tests on sample productions and are not legally binding.

### ARTICLES, DIMENSIONS AND BARCODES

	dimensions	pieces per box	barcode
Washi Tape LT:	19 mm x 50 m	48 rolls	8051499033668
Washi Tape LT:	25 mm x 50 m	36 rolls	8051499033613
Washi Tape LT:	30 mm x 50 m	32 rolls	8051499033620
Washi Tape LT:	38 mm x 50 m	24 rolls	8051499033798
Washi Tape LT:	50 mm x 50 m	24 rolls	8051499033828

### OUR PROPOSAL OF PACKAGING

- Sleeve with B/W or coloured (up to 5 colours) barcode label.
- Harmonica.

### RECOMMENDATIONS

It's a good rule to use the product within 6 months from purchase, because the unwinding force of the tape increases with time. The product must be stored in its box in a dry location protected from sunlight, at about 15 °C - 25 °C and 50% relative humidity. If stored in different conditions, the product must be reconditioned. After application, the removal of the tape must be done slowly without tears. Before applying the tape, always check if the surface is clean. Euromask disclaims any liability for any direct or indirect damage coming from the misuse of the product. Under normal conditions, the tape is not toxic and is not approved for medical use.

The a.m. values may be changed at any moment for production needs or technical updates.



rev. 01\_Jan 2024